

FICHE TECHNIQUE

Série TA604 - 4 canaux

Amplificateur Classe D



Séries TA604 - 4 canaux Amplificateurs Classe D

MODEL	TA604
Number of Channels	4
Output Power per Channel, 4 Ω	150 W
Output Power per Channel, 8 Ω	75 W
Frequency Range	20 Hz- 20 kHz
Sensitivity	0.775 V
Total Harmonic Distortion	0.02% (20 Hz - 20 kHz)
Crosstalk	60 dB (1 kHz)
Signal-to-Noise Ratio	100 dB (unweighted)
Input Impedance	10 kOhms (balanced)
Power Requirements	~ 230 V, 50/60 Hz
Height	1U
Depth in Rack	295
Dimensions (W,H,D)	478 x 44 x 300
Weight	4.2 kg
Power Consumption:	
- Pink noise, 1/8 power @ 4 Ω	120W
- STBY	9W

MODEL	TA604DL
Number of Channels	4
Output Power per Channel, 70/100 V	150 W
Frequency Range	100 Hz - 20 kHz HPF 100 Hz 24 dB/oct
Sensitivity	0.775 V
Total Harmonic Distortion	0.02% (20 Hz - 20 kHz)
Crosstalk	60 dB (1 kHz)
Signal-to-Noise Ratio	100 dB (unweighted)
Input Impedance	10 kOhms (balanced)
Power Requirements	~ 230 V, 50/60 Hz
Height	1U
Depth in Rack	295
Dimensions (W,H,D)	478 x 44 x 300
Weight	9.4 kg
Power Consumption:	
- Pink noise, 1/8 power @ 4Ω	120W
- STBY	14W
DSP engine	
- Sampling Rate	48 kHz
- DAC / ADC	24-bit
- Internal Processing	56-bit

